

通过ISO9001国际质量体系认证

# PZ1740E

ONE-COLOR SHEETFEED OFFSET PRESS



景德 JINGDE



江西中景集团有限公司  
JIANGXI ZHONGJING GROUP CO.,LTD.

## 结构特点

- 本机纸张适应性强, 可满足用户大规格纸张的印刷。
- 主传动采用变频调速, 控制电路采用自动程序操作。
- 主机设有正点、反点、低速运行按钮, 便于操作者观察和调整机器, 方便滚筒的清洁、擦洗。
- 递纸机构采用共轭凸轮组和恒力装置, 保证了纸张传递平稳、准确、可靠, 机器运转噪音小。
- 快速夹版装置缩短了印刷作业辅助时间。
- 输纸头采用获得国家专利的旋转式分气阀, 具有自动清除纸毛、灰尘的功能。
- 新型节气式纸张减速器保证了高速收纸整齐。
- 采用定点、定量、定时自动集中润滑系统, 润滑充分, 增强了机械安全运行的可靠性。
- 电气设有干扰(故障)诊断显示, 便于寻找干扰源, 及时排除故障。
- 墨辊排列方式更趋于合理, 匀墨效果好, 墨色均匀、稳定。

# PZ1740E



## ONE-COLOR SHEETFED OFFSET PRESS

### Construction Features

- The press is designed to print on a wide range of stock thereby giving the printer the capability to satisfy the various demands of their customers.
- The Press Drive is infinitely variable within parameters (3,000 – 12,000 s/p/h), based on the design of the electric motor and inverter.
- The forward inch and reverse inch buttons allow the operator to conveniently adjust or clean all press cylinders.
- The up-swing gripper with a positive pressure cam assembly ensures that the infeed and transfer of sheets at high speeds are done stably, accurately and reliably
- The quick-action plate clamping system shortens the make-ready time.
- The feeder head is equipped with a patented suction head valve that automatically cleans the paper lint and dust.
- The advanced vacuum sheet brake system / sheet slow-down device allows the sheets to be delivered smoothly, even at high speeds.
- The central lubrication system automatically oils the press at the specific and necessary positions and intervals, ensuring the long-term reliability of the press.
- The Feeder Control Console displays all press faults so that the operator can easily troubleshoot the fault source and correct the problem.
- The advanced design of the inker ensures the uniformity of lay-down of the ink on the substrate.

### 主要技术参数SPECIFICATIONS:

机型 Model	PZ1740E
最高机器速度(张/时) Maximum machine speed	12,000s.p.h
最大用纸尺寸 Maximum sheet size	520 × 740mm
最小用纸尺寸 Minimum sheet size	273 × 370mm
印刷纸张厚度 Sheet thickness	0.04–0.45mm
最大印刷面积 Maximum image area	510 × 730mm
印版尺寸 Plate size	625 × 755 × 0.3mm
橡皮布尺寸 Blanket size	680 × 755 × 1.9mm
给纸堆最大高度 Maximum feeder pile height	930mm
收纸堆最大高度 Maximum delivery pile height	420mm
外型尺寸(长×宽×高) Machine overall dimension	2350 × 2040 × 1835mm
电机总功率 Total power of motors	6.79Kw
机器总重量(约) Machine gross weight (Approx.)	3700kg

产品如有改动, 不另行通知用户

THE PRODUCTS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

## 江西中景集团有限公司

JIANGXI ZHONGJING GROUP CO., LTD.

中国江西省景德镇市新厂陶阳路76号  
TEL: 0798-8441724 8446342 8471880  
E-Mail: zjzt@public1.jd.jx.cn

76 Taoyang Road Xinchang Jingdezhen Jiangxi, China  
FAX: 0798-8441654 8446343 PC: 333001  
http://www.zjzt.net