



WIN500 单面胶印机 WIN500 OFFSET PRESS



威海印刷机械有限公司
WEIHAI PRINTING MACHINERY CO., LTD.

WIN500 单面胶印机

WIN500 OFFSET PRESS

横进纸、大纸幅、功能更全，更适应彩色印刷

LATERAL FEEDING,LARGE PAPER,SUITABLE FOR COLOR PRINTING

印刷版材可用PS版、氧化锌版、水性版。产品质量可靠，匀墨效果优良，印品层次分明，定位准确，是快速印刷的理想设备。

Ps-plate,zinc oxide plate,water form plate could be used with this machine.With the advantage of reliable quality,easy adjustment and operation,this machine is one of the ideal equipment to be used for good quality quick printing.

特点

- ★横进纸，走纸稳，无皱，保证定位更准确。
- ★2张单张高速给纸。
- ★双弹簧叼纸牙，更适合于大基地印刷。
- ★独特设计的天地调整，无需推扶滚筒，减少印刷辅助时间，印刷更省力。
- ★同类机型独有的版滚筒自动离合压。
- ★独特的防划痕，防蹭脏装置。
- ★采用镀铬的印刷滚筒，滚筒结构更合理。
- 采用铸铁墙板，结构坚固耐用，强度高，韧性好，保证印刷压力。
- 不锈钢水辊，水胶辊润版系统，水量可无限调节。
- 方便的墨辊清洗系统，更换墨色快速。
- 采用与大型机相媲美的对置滚轮式拉纸装置，可进行精确的对印。
- 操作侧有微动按钮，在印刷过程中也可进行套准调整。
- 先进的给纸收纸故障检测控制装置。
- 静电消除装置，可在温湿度变化时消除纸张静电。
- 喷粉装置，可避免高速印刷时印品沾脏或背污。
- 具有安全防护装置，确保安全生产。
- 采用功率大的变频调速电机，PLC电源程序控制装置。

FEATURES

- ★ Lateral feeding,paper moving stably,no-wrinkles,positioning more exactly.
- ★ Has the function of feeding one sheet of paper as machine rotate two cycles.
- ★ Double-spring grippers,suitable for large width printing.
- ★ Unique adjusted method,cannot clean the blanket cylinders when doing vertical image adjustment,save your time.
- ★ Unique plate cylinder on-off mechanism.
- ★ Unique avoiding scratching and dirty device.
- ★ Chrome-plated cylinders,cylinders structure more reasonable.
- With cast-iron frame,straight construction ensuring high impression pressure.
- Stainless steel water fountain roller,roller dampening system,stepless adjusting volume of water supply.
- Coordinated ink roller cleaning system makes ink change much quick.
- Roller-turndrive gear guide mechanism ensures precision image positioning.
- Image position can be micro-adjusted during printing.
- Advanced feed paper and delivery problem detecting device.
- Static electricity eliminant can be equipped.
- Powder spray device is included for anti-offset at high speed printing.
- Safety protection starts to make sure of safety operation.
- Inverter controlled motor,PLC device.

技术参数 SPECIFICATIONS

| | |
|-----------------------------|---|
| 最大纸张尺寸 Paper size (Max.) | 500mm × 365mm |
| 最小纸张尺寸 Paper size (Min.) | 90mm × 140mm |
| 纸厚范围 Paper thickness | 0.04mm - 0.3mm |
| 最大印刷面积 Printing area (Max.) | 470mm × 350mm |
| 印刷速度 Printing speed | 3000s/h - 9000s/h |
| 最大印版 Plate size | 490mm × 400mm |
| 橡皮布尺寸 Blanket size | 496mm × 422mm × 1.65mm |
| 给纸方式 Feeding system | 气动给纸 (12个吸嘴) Automatic vacuum feed system(with 12 suction feet) |
| 收纸方式 Delivery system | 链条收纸 Chain delivery |
| 水墨辊 Number of rollers | 14个 (10个墨辊, 4个水辊) 14rollers(Ink rollers:10 Water rollers:4) |
| 润版方式 Dampening system | 水墨分开 Molleton |
| 电源 Power source | 220V/50Hz 主电机 0.75Kw, 气泵电机 0.42Kw Main motor 0.75Kw Pump motor 0.42Kw |
| 外型尺寸 Dimensions (L × W × H) | 1900mm × 1100mm × 1400mm |
| 重量 Net weight | 660Kg |

●设计和规格有时会发生变更，恕不预告。-Specifications are subject to change without notice.

威海印刷机械有限公司 WEIHAI PRINTING MACHINERY CO., LTD.

地址: 中国山东省威海市解放路38号 38,JIEFANG RD, WEIHAI, SHANDONG, CHINA

电话: 0631-5223224 5229449 邮编: 264200 Tel:0631-5223224 5229449 P.C:264200

传真: 0631-5223813 5225023 Fax:0631-5223813 5225023

E-mail:sdwhyj@wh-public.sd.cninfo.net